



LEGEND

- A. #16 AWG (19 x #29 AWG) SILVER PLATED COPPER.
- B. SILICONE RUBBER
- C. SEMICONDUCTIVE INK & TAPE (0.0055 THK, 1/2 LAPPED).
- D. SHIELD, #34 AWG T.C. 6/16, 86% COVERAGE.
- E. JACKET

RATING: MAIN LAYER 15KVAC RMS, 50KVDC

JACKET TYPE	DEFINTION	COLOR	WALL	OD
N	NEOPRENE RUBBER	BLACK	0.06	0.45
S	SILICONE RUBBER	RED	0.06	0.45
T	THERMOPLASTIC RUBBER	BLACK	0.04	0.41
V	VINYL	BLACK	0.04	0.41

REVISIONS

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE THE PROPERTY OF DIELECTRIC SCIENCES, INC AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF APPARATUS WITHOUT PERMISSION.

REV	ECO NUMBER	APPD	DATE	UNLESS OTHERWISE SPECIFIED
-	RELEASE DRAWING			DIMENSIONS ARE IN INCHES TOLERANCE ON DECIMALS ANGLES .XX ±.01 ± .XXX ±.005
				CONCENTRICITY .005 TIR REMOVE BURRS & SHARP EDGES ALL MACHINE SURFACES 125 \checkmark

DRAWN O. ABDULKY	DATE 30OCT07
CHECKED	DATE
APPROVED	DATE
MATERIAL	
FINISH	

DIELECTRIC SCIENCES, INC
CHELMSFORD, MASSACHUSETTS 01824

CABLE: 1/C 16 AWG, 30 KVDC

SIZE A	FSCM NO. 50509	DWG NO. 2215SJ	REV
SCALE		SHEET 1 OF 1	